

Quality, Consistency & Support

TECHNICAL INFORMATION SHEET: CAUSTIC SODA LIQUOR 70 Tw

Description

Caustic Soda Liquor 70 Tw is a 32% solution of Sodium Hydroxide and is designed for use in brewery vessel cleaning.

COMMODITY CODE:

PRODUCT NAME:

CAUSTIC SODA

PRODUCT CODE:

LIQUOR 70Tw

CAUSOD70

28151100

PACKAGING: 25, 200, 1350 KG

Benefits

Caustic Soda Liquor 70 Tw is designed for use in the mash tun, mash vessel, decoction vessel, cereal cookers, mash filters, boiling kettles, hops strainer and many other areas. It is suitable for stainless steel and can be used at high temperatures (max temp being 80°C).

This product is ideal for the removal of protein, dextrin, gum cellulose, hemicelloses, mucilage, pectin, tannin and mineral salt deposition and scaling.



TECHNICAL SUPPORTtel: +44 (0) 115 978 5494 | e: techsupport@murphyandson.co.uk

REGULATORY COMPLIANCE INFORMATION Refer to the **Product Specification Sheet** or contact us on tel: +44 (0) 115 978 5494 | e: <u>compliance@murphyandson.co.uk</u>

HEALTH & SAFETY INFORMATION

Refer to the Safety Data Sheet (SDS)

Murphy & Son Limited, Alpine Street, Old Basford, Nottingham NG6 0HQ United Kingdom
 Tel:
 (+44) 115 978 5494

 Fax:
 (+44) 115 924 4654

 Email:
 info@murphyandson.co.uk

 Web:
 www.murphyandson.co.uk

Registered in England No. 106442 VAT No. 196 8782 88





Quality, Consistency & Support

Guidelines for use

- Check that the product is within its shelf life before use,
- Care should be taken to avoid contact with eyes and skin by the use of suitable gloves and googles
- In case of contact with skin or eyes wash with plenty of water
- Read the Safety Data Sheet prior to use
- Wash spillages to drain with plenty of water
- It is not suitable for use on aluminium, zinc, tin or their alloys

Application and rates of use

Caustic Soda Liquor 70 Tw is 32% sodium hydroxide and should be added to water to give a final concentration as caustic of 1-2%. Therefore three to six litres of Caustic Soda Liquor 70 Tw per hl of water is required.

Where hardness of water is greater than 200 mg/litre as CaCO₃, an additional sequesterant may be required to provide the necessary sequestering power such as Murphy's Sequesterant Additive, please ask our sales team for more information regarding this product or if you are interested in having your water hardness tested.

Storage and shelf life

- Store in cool, dry conditions away from direct sunlight and acids
- Keep container sealed when not in use
- Recommended storage temperature is 10°C (minimum °4 C, maximum 15°C)
- The shelf life at the recommended storage temperature is two years from date of manufacture.

PRODUCT	CAUSTIC SODA LIQUOR 70 Tw	PRODUCT CODE	CAUSOD70
ISSUE No.	3	DATE	29/8/18
WRITTEN BY	E Wray	AUTHORISED BY	RJ Haywood

